

Product Data Sheet

E-STEP WALKWAY MAT Accessories

Non-slip mat to provide safe access for flat roof maintenance and to designate frequently accessed areas on Ecoflex / Ecoline PVC roofs

E-Step Walkway Mat is specially engineered for roof walkways. It is a two-layer matting that protects the PVC roof membrane and provides safe rooftop access. It is made from non-porous PVC with cross directional top ribs and a 'diamond cut' surface for a firm underfoot grip.

E-Step Walkway Mat carries a high R10 slip resistant rating under DIN 51130.

It is impermeable in all weathers and when laid flat will remain stable in winds up to 60 mph / 96 km/h.

Key benefits

- Certified slip resistance DIN 51130: R10 ASTM 1677: 1.0/0.9
- Compatible with PVC roof membranes
- Roof membrane protection
- Excellent drainage DIN 51120: V10
- Fast installation – loose lay, no fixing required
- Contours to roof structure
- Robust and long-lasting

Features

- Durable one-piece construction
- Diamond cut pattern
- Supplied in 10m rolls
- Made from flexible PVC
- Stable in winds up to 60 mph (96 km/h)
- UV resistant

Standard Sizes and Colours

- Colours:** Available in light grey and black. Other colours available on request.
- Standard roll options:** 10 x 0.6m / 10 x 0.91m / 10 x 1.22m
- Height:** 14mm
- Weight:** 6.6 kg/m²

General

- Appearance:** Open grid 'duckboard' design with cross directional top ribs.
- Durability:** One-piece welded construction for long life and minimal maintenance.
- Installation:** Loose laid. PVC ramp edging available in 6cm and 10cm widths. When loose laid, E-step is effective for winds up to 60 mph (96 km/h).
- Workability:** Flexible; easy to cut and shape on site.
Supplied in rolls with top ribs facing outwards. Requires inverting once rolled out prior to use.

Technical Data

ACOUSTIC	Excellent sound absorption properties.
CHEMICAL	Resistant to most acids, alkalines and oils.
COMPOSITION	Flexible plasticised Polyvinyl Chloride (PVC).
ENVIRONMENT	Black colour is manufactured with post-industrial recycled material. Recycled content averages at least 30% but 100% is the objective where possible. E-Step does not use any substances currently included in the SVHC list under REACH in any matting products. E-Step is 100% recyclable.
FIRE	EN ISO 13501-1:20007 – CfI-SI.
HYGIENE	Non-porous 100% PVC. Inhibits growth of bacteria.
REVERSION	Thermoplastic shrinkage can result in size reductions up to 2%. Accelerated in hot environments.
SLIP RESISTANCE	ASTM F 1677 – Dry/Wet: 1.0 / 0.9
	DIN 51130: R10, V10
THERMAL	Functional -23°C+60°C (slight size variation may occur at temperature extremes).
UV LIGHT	Resistance to PVC degradation.
WIND RESISTANCE	When loose laid, E-Step is effective for winds up to 60 mph (96 km/h). In laboratory conditions on a flat, stable platform, the product has remained stable in wind speeds up to 94 mph.

For information on ancillary products (edging strip, connector clips, snap track, hooks), please contact Axter Ltd.

The manufacturer reserves the right without prior notice to modify the composition of this product. The information provided is not intended to form any part of a contract or provide a guarantee and users should check if there have been any changes to the information above since publication of this document. Characteristics provided in this publication derive from data obtained under controlled test conditions. Axter Ltd makes no warranties, express or implied, as to the properties and performance under any variations from such conditions in actual construction.