


1	Hard edge by specialist contractor
2	ECOMETAL® preformed PVC coated metal trim mechanical (MTP) fixing at 200mm ctrs (by specialist subcontractor)
3	ECO/R coverstrip
4	Heat welded seam - 40mm
5	FM/D contact adhesive
6	ECOFLEX® FM single ply membrane
7	Restraint bar and mechanical (C) fixing
8	ECOFLEX® ADH fleeceback single ply membrane fully bonded using ADH adhesive
9	ADH adhesive
10	HYTHERM® ADH tapered / flat board insulation fully bonded using Hyra-Stik EVO adhesive (thickness to achieve design U-value and/or minimum 1:40 design fall)
11	ECOFLEX® air & vapour control layer (AVCL)
12	Vernis Antac ST Primer
13	Plywood roof deck by specialist contractor
14	Metal coping (design option)
15	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® ADH TYPICAL PARAPET
UPSTAND DETAIL

DWG.No
WR.P.EF.adh.60

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)
N/A

STANDARD DETAIL