


1	ECOFLEX® ADH single ply membrane single ply membrane fully bonded using adh adhesive
2	ADH adhesive
3	HYTHERM® ADH tapered / flat board insulation fully bonded using Hyra-Stik EVO adhesive (thickness to achieve design U-value and/or minimum 1:40 design fall)
4	Heat welded seam - 40mm
5	ECO/R cover strip
6	Hard edge by specialist contractor
7	ECOMETAL® preformed PVC coated metal trim mechanical (MTP) fixing at 200mm ctrs
8	Lead apron flashing (by specialist subcontractor)
9	ECOFLEX® air & vapour control layer (AVCL)
10	Vernis Antac ST Primer
11	Plywood roof deck by specialist contractor
12	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)
13	Pitched roof by specialist contractor



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A
CLIENT : N/A
DRAWING : ECOFLEX® ADH TYPICAL MANSARD
EDGE DRIP DETAIL

DWG.No
WR.P.EF.adh.110

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)
N/A

STANDARD DETAIL

Ef

Ecoflex