


1	ECOFLEX® FM single ply membrane
2	ADH adhesive
3	HYTHERM® ADH tapered / flat board insulation fully bonded using Hyra-Stik EVO adhesive (thickness to achieve design U-value and/or minimum 1:40 design fall)
4	Heat welded seam - 40mm
5	ECOFLEX® tubular washer and mechanical fastener (C) fixing
6	Galvanised metal sleeve flashing mechanically fixed and sealed at perimeter (by specialist subcontractor)
7	Vernis Antac ST Primer
8	ECOFLEX® air & vapour control layer (AVCL)
9	Plywood roof deck by specialist contractor
10	SVP by specialist contractor
11	Weathering cowl by specialist contractor
12	Jubilee clip with suitable sealant under constant compression
13	ECO/D non-reinforced membrane collar





www.axterhd.co.uk
info@axterhd.co.uk
01473 724056

Axter Ltd.
West Road, Ransomes European,
Ipswich, Suffolk, IP3 9DX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® ADH TYPICAL SVP PENETRATION WITH WEATHERING COWL DETAIL

DWG.No

WR.P.EF.adh.91

SCALE

1:5 @ A4

DATE

2019

REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex