


1	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
2	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
3	Heat welded seam - 40mm
4	ECOFLEX® FM single ply membrane
5	FM/D contact adhesive
6	ECOMETAL® preformed PVC coated metal trim mechanical (MTP) fixing at 200mm ctrs
7	Non-combustable support (fixed to one side only) by specialist contractor
8	Packers to top by other
9	Non-flammable compressible foam
10	Sealant
11	ECO/R cover strip
12	Batten by specialist contractor
13	ECOFLEX® air & vapour control layer (AVCL)
14	Vernis Antac ST Primer
15	Metal roof deck by specialist contractor
16	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)
17	Restraint bar and mechanical (C) fixing



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A
CLIENT : N/A
DRAWING : ECOFLEX® FM TYPICAL MOVEMENT
JOINT - TWIN KERB DETAIL

DWG.No
WR.M.EF.fm.130

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex