

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL INTERNAL GUTTER
DETAIL

DWG.No

WR.M.EF.fm.190

SCALE

1:5 @ A4

DATE

2019



REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex



| | |
|----|--|
| 1 | ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings |
| 2 | HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall) |
| 3 | Heat welded seam - 40mm |
| 4 | ECOMETAL® preformed PVC coated metal with mechanical (C) fixings at 200mm ctrs |
| 5 | ECO/R cover strip |
| 6 | Restraint bar and mechanical (C) fixing |
| 7 | ECOFLEX® air & vapour control layer (AVCL) |
| 8 | Vernis antac ST primer |
| 9 | Metal roof deck by specialist contractor |
| 10 | Mechanically fixed hard edge by specialist subcontractor |