

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DWG.No

WR.M.EF.fm.120

SCALE

1:5 @ A4

DATE

2019

REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex

DRAWING : ECOFLEX® FM TYPICAL PITCHED TO FLAT ROOF ABUTMENT DETAIL (INSULATED)

1	Batten and tiles / slates (by specialist subcontractor)
2	Sarking felt (by specialist subcontractor)
3	Non-combustable support by specialist contractor
4	FM/D contact adhesive
5	Restaint bar, cord and mechanical (MTP) fixing
6	ECOFLEX® FM single ply membrane
7	Heat welded seam - 40mm
8	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
9	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
10	ECOFLEX® air & vapour control layer (AVCL)
11	ECOFLEX® air & vapour control layer (AVCL)
12	Metal roof deck by specialist contractor
13	ECO/200 separation membrane (taped)

