


|    |  |
|----|--|
| 1  | DPC/cavity tray/weep holes to drain internally or externally as specified  |
| 2  | ECOFLEX® sealant   |
| 3  | ECOMETAL® preformed PVC coated metal trim mechanical (C) fixing at 200mm ctrs  |
| 4  | FM/D contact adhesive  |
| 5  | ECOFLEX® FM single ply membrane  |
| 6  | ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings  |
| 7  | HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall) |
| 8  | Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)  |
| 9  | Restraint bar and mechanical (C) fixing  |
| 10 | Heat welded seam - 40mm  |
| 11 | ECOFLEX® air & vapour control layer (AVCL)   |
| 12 | Vernis antac ST primer   |
| 13 | Metal roof deck by specialist contractor   |





www.axterhd.co.uk  
info@axterhd.co.uk  
01473 724056

Axter Ltd.  
Weal Road, Ransomes European,  
Ipswich, Suffolk, IP3 9SX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL SKIRTING UPSTAND TO BRICK PARAPET DETAIL

DWG.No

WR.M.EF.fm.10

SCALE

1:5 @ A4

DATE

2019

REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex