


1	Window/Door joinery by others
2	ECOFLEX® sealant
3	ECOMETAL® preformed PVC coated metal trim mechanical (C) fixing at 200mm ctrs
4	FM/D contact adhesive
5	ECOFLEX® FM single ply membrane
6	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
7	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
8	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)
9	Restraint bar and mechanical (C) fixing
10	Heat welded seam - 40mm
11	ECOFLEX® air & vapour control layer (AVCL)
12	Vernis antic ST primer
13	Metal roof deck by specialist contractor



www.axterhd.co.uk
info@axterhd.co.uk
01473 724056
Axter Ltd.
West Road, Ransomes European,
Ipswich, Suffolk, IP3 9SX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL INSULATED SKIRTING UPSTAND TO DOOR/WINDOW CILL DETAIL

DWG.No
WR.M.EF.fm.21

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)
N/A

STANDARD DETAIL

Ef

Ecoflex