


1	ECOFLEX® ADH fleeceback single ply membrane fully bonded using ADH adhesive
2	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
3	ECOFLEX® air & vapour control layer (AVCL)
4	Vernis Antac ST Primer
5	ECOFLEX® tubular washer and mechanical fastener (C) fixing
6	Longitudinal /Transversal Lap Joint (with heat welded seam - 40mm)
7	Metal roof deck by specialist contractor





www.axterhd.co.uk
info@axterhd.co.uk
01473 724056

Axter Ltd
West Road, Ramsgate, Kent, UK
TN11 9BX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL TRANSVERSAL / LONGITUDINAL & HEAD LAP JOINT DETAIL

DWG.No
WR.M.EF.fm.140

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex