


1	Heat welded seam - 40mm
2	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
3	ECO/R cover strip
4	ECOMETAL® preformed PVC coated metal trim as hard edge
5	ECOFLEX® FM single ply membrane
6	Restraint bar and mechanical (C) fixing
7	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
8	ECOFLEX® air & vapour control layer (AVCL)
9	Vernis Antac ST Primer
10	Metal roof deck by specialist contractor
11	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)



www.axterhd.co.uk  
info@axterhd.co.uk  
01473 724056

Axter Ltd.  
West Road, Ransomes European,  
Ipswich, Suffolk, IP3 9SX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL CHANGE IN ROOF LEVEL, BOX GUTTER EDGE DETAIL

DWG.No  
WR.M.EF.fm.100

SCALE  
1:5 @ A4

DATE  
2019

REV (if applicable)  
N/A

STANDARD DETAIL

Ef

Ecoflex