


1	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
2	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
3	Preformed PVC membrane flange
4	Heat welded seam to field membrane
5	Vent pipe by specialist contractor
6	ECOFLEX® tubular washer and mechanical fastener (C) fixing
7	Galvanised metal sleeve flashing mechanically fixed and sealed at perimeter (by specialist subcontractor)
8	ECOFLEX® air & vapour control layer (AVCL)
9	Vernis Antac ST Primer
10	Metal roof deck by specialist contractor
11	AXTER® prefabricated vent pipe



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A
CLIENT : N/A
DRAWING : ECOFLEX® FM TYPICAL SVP PENETRATION
WITH INTEGRAL FLANGE DETAIL

DWG.No
WR.M.EF.fm.92

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)

N/A

STANDARD DETAIL

Ef

Ecoflex