


1	DPC/cavity tray/weep holes to drain internally or externally as specified
2	ECOFLEX® sealant
3	ECOMETAL® preformed PVC coated metal trim mechanical (C) fixing at 200mm ctrs
4	FM/D contact adhesive
5	ECOFLEX® FM single ply membrane
6	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
7	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)
8	Restraint bar and mechanical (C) fixing
9	Heat welded seam - 40mm
10	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
11	ECOFLEX® air & vapour control layer (AVCL)
12	Vernis Antac ST primer
13	Metal roof deck by specialist contractor





www.axterhd.co.uk  
info@axterhd.co.uk  
01473 724056
Axter Ltd  
West Road, Ransomes European,  
Ipswich, Suffolk, IP3 9SX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A  
 CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL INSULATED SKIRTING UPSTAND TO BRICK PARAPET  
 DETAIL

DWG.No  
 WR.M.EF.fm.20

SCALE  
 1:5 @ A4

DATE  
 2019

REV (if applicable)  
 N/A

STANDARD DETAIL



Ecoflex