


1	ECOFLEX® FM single ply membrane mechanically fixed with ECOFLEX® membrane washers and (C) fixings
2	HYTHERM® tapered / flat board insulation mechanically fixed with ECOFLEX® insulation washers and fixings (thickness to achieve design U-value and/or minimum 1:40 design fall)
3	ECOFLEX® air & vapour control layer (AVCL)
4	Vernis Antac ST primer
5	Metal roof deck by specialist contractor
6	Heat welded seam - 40mm
7	Galvanised bent metal angle mechanically fixed at perimeter (by specialist subcontractor)
8	Hard edge by specialist contractor
9	ECO/R cover strip
10	ECOMETAL® preformed PVC coated metal trim mechanical (MTP) fixing at 200mm ctrs
11	Guttering by others
12	Facia board



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : ECOFLEX® FM TYPICAL DRIP TO GUTTER

DETAIL

DWG.No

WR.M.EF.fm.40

SCALE

1:5 @ A4

DATE

2019

REV (if applicable)

N/A

STANDARD DETAIL