


1	ECOLINE® FM single ply membrane
2	ADH Adhesive
3	HYTHERM® tapered / flat board insulation fully bonded using Hyra-Stik adhesive (thickness to achieve design U-value and/or design fall)
4	Heat welded seam - 40mm
5	ECOLINE® tubular washer and mechanical fastener (C) fixing
6	Galvanised metal sleeve flashing mechanically fixed and sealed at perimeter (by specialist subcontractor)
7	Vernis Antac ST Primer
8	ECOLINE® air & vapour control layer (AVCL)
9	Plywood roof deck by specialist contractor
10	SVP by specialist contractor
11	Weathering cowl by specialist contractor
12	Jubilee clip with suitable sealant under constant compression
13	ECO/D non-reinforced membrane collar



Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A  
CLIENT : N/A  
DRAWING : ECOLINE® ADH TYPICAL SVP PENETRATION WITH WEATHERING COWL DETAIL

DWG.No  
**WR.P.EL.adh.91**

SCALE  
**1:5 @ A4**

DATE  
**2019**

REV (if applicable)  
**N/A**

STANDARD DETAIL

**EI**

Ecoline