1	40mm - 60mm river washed gravel ballast (no fines) minimum 85kg/m
2	AXTER® water reducing membrane
3	AXTER® inverted roof insulation system to achieve the required design U-Value
4	Vernis Seal primer (100 to 150 g/m²)
5	FORCE® 4000 DALLE
6	AXTER® Butyl Cord
7	AXTER® Armalu aluminium faced membrane
8	This area to be fully bonded by torching method
9	AXTER® EXCEL® Joint 50
10	Concrete roof slab by specialist contractor laid to zero fall (roof with a slope which lies between 0 and 1:80)



AXTER
www.axterltd.co.uk
info@axterltd.co.uk
01473 724058
Axter Ltd,
West Road, Ransomes Europark,
Ipswich, Suffolk, IP3 9SX

Axter provide detail drawings as part of our technical design service. Such drawings should only be used as a guide during the design process and should not be utilised during construction. Axter accepts no liability for misuse of this service.

PROJECT : N/A

CLIENT : N/A

DRAWING : FORCE DALLE® TYPICAL EXPANSION JOINT DETAIL

DWG.No
FD.C.0516.100.Bal

SCALE
1:5 @ A4

DATE
2019

REV (if applicable)
N/A

STANDARD DETAIL

F.d

Force Dalle