

Technical Data Sheet

GRANULE/CHIPPING ADHESIVE

Adhesive

Presentation	Granule adhesive is a dispersion in aqueous phase of vinyl acrylic polymers.
Usage	<p>To adhere extra granules / mineral chippings to the surface of a bitumen waterproofing membrane for aesthetic purposes.</p> <p>Installation technique:</p> <p>Carefully brush the surface of the membrane.</p> <p>Spread the granule / chipping adhesive with a squeegee at the rate of 200 to 500 g/m².</p> <p>Manually sprinkle the extra granules / chippings over the membrane (1.2 to 1.5 kg/m²).</p> <p>With a roller press in the extra granules / chippings.</p> <p>Leave to dry for a minimum of 24 hours, depending on weather conditions, then remove excess granules / chippings by careful brushing.</p> <p>Repeat the process if required.</p> <p>Tools can be cleaned in water.</p>
Packaging	5kg drum.
Storage	<p>This product should be stored in a well ventilated place protected from very warm or very cold conditions.</p> <p>Maximum storage : 6 months (in original sealed packaging).</p> <p>Production and expiry dates are clearly shown on the can.</p>

Safety

This product should not be used if the temperature of the substrate is lower than 5°C or in rainy conditions.

Safety precautions to be observed when using this product are given in the Material Safety Data Sheet.

Characteristics	Method	Units	Values	Tolerance
Density			1	± 0.05
Dry extract		%	50	± 1
Viscosity at 25 °C T4V10		cPo	600	
Colour			Milky white	

The manufacturer reserves the right to modify, at any time, the characteristics of this product.