

Technical Data Sheet

MASTIC HYRENE Adhesive

Description	MASTIC HYRENE is a cold applied bituminous adhesive with added solvents.
Usage	<p>Adhesive (spots or strips) for thermal insulation boards (PIR, PUR, EPS) - 500g/m², to be increased according to wind load - under non ballasted and ballasted waterproofing systems.</p> <p>Used for partially bonding waterproofing membranes with sanded under surface on to concrete decks.</p> <p>Cleaning tools: petroleum solvents (eg. White Spirit)</p>
Packaging	25 kg drums with plastic lining bag inside.
Storage	<p>Store in a cool ventilated area.</p> <p>Protect from heat and keep away from any source of flame or spark.</p> <p>Maximum storage period : 2 years (in unopened original packaging).</p>
Safety Information	<p>This product contains flammable products.</p> <p>Safety precautions to be taken when using this product are described in the MASTIC HYRENE safety data sheet.</p>

Characteristics	Method	Units	Values	Tolerance
Density			1.2	± 0.05
Solid content		%	87	± 2
Viscosity at 25 °C	T6V10	cps	40 000 to 50 000	
Colour			Black	
Consistency			Smooth semi-liquid	

The manufacturer reserves the right to modify, at any time, the characteristics of this product.