

Technical Data Sheet

MATCOAT R Reinforcement

Description	MATCOAT R is a nylon jersey woven reinforcement and is used in combination with the STARCOAT R liquid system for waterproofing details.
Use	Used as a reinforcement in the STARCOAT R liquid waterproofing system for: Upstands, roof penetrations, columns, balustrade points, curbs, perimeters, pipes and all other irregular penetrations. The STARCOAT R system achieves a watertight, durable UV and puncture resistant, flame free (cold applied) liquid detailing solution and can be treated with mineral granules to seamlessly complement the existing or new waterproofing.
Application method	Unroll the MATCOAT R over the surface to be covered, position it carefully and cut to the required size. Next apply a layer of pre-prepared cool STARCOAT R. With a dry brush press the MATCOAT R thoroughly into position to make sure it is fully bonded and to eliminate blisters formed during polymerization. Minimum lap between two layers of MATCOAT R is 10mm. The second layer of STARCOAT R is then applied and covers the MATCOAT R reinforcement.
Packaging	Roll size: 50m x 0.15m
Storage	Rolls must be stored in a cool, dry place and should not be exposed to moisture, direct sunlight or severe temperature variations. Rolls should be stored at a temperature between 5°C to 35°C.

CHARACTERISTICS	
Mass per unit area	> 70g/m ²
Tensile strength: (DIN 53857)	66 N/cm
Elongation at break (DIN 53857)	75%

The manufacturer reserves the right to modify, without prior warning, the characteristics of this product.
No responsibility will be taken by Axter Ltd for incorrect use of this product.