

Technical Data Sheet

STICKBAND Reinforcements and Tapes

Introduction

Stickband is a self-adhesive waterproofing strip made up of a mastic butyl-based, self-adhesive binder and protected by an aluminium foil. The under surface is a peel-off silicone film. Thickness is approximately 0.6mm.

Use

In particular for use with the Axter Wilotekt-Plus® structural waterproofing system to seal gaps in the substrate. Also used on new and refurbishment projects to achieve the following:

- waterproof joints on metal decks (air and vapour control layer for profiled metal decks); channels, gutters, pipework, rainwater outlets, kerbs, covers (zinc, aluminium, galvanised steel, lead);
- waterproofing for other detailing work (bridging cracks, flashings, etc).
- sealing glazing joints: canopies, verandas, sheeds, window and door frames, rooflights, domes.

Stickband is cold bonded to decks that are clean, dry, sound (not porous or friable) without a primer. If the deck is porous or friable, apply primer (Vernis Antac 300g/m²).

Packaging

Stickband is available in the following roll sizes:

- 10m x 5cm , average weight 0.55 kg (12 rolls/box)
- 10m x 7.5cm , average weight 0.825 kg (8 rolls/box)
- 10m x 10cm , average weight 1.100 kg (6 rolls/box)
- 10m x 15cm , average weight 1.650 kg (4 rolls/box)
- 10m x 20cm , average weight 2,200 kg (3 rolls/box)
- 10m x 30cm , average weight 3.300 kg (2 rolls/box)
- 10m x 45cm , average weight 4.950 kg (4 rolls/box)

| | | |
|--------------------|--|------------------------|
| Storage | Rolls must be stored in cardboard box in a dry, ventilated place, in a maximum temperature of 30°C, away from any source of heat or fire, for a maximum period of 12 months. Storage in temperatures above 30°C can cause problems when removing the silicone during installation. Rolls must be protected from frost. | |
| Composition | Binder : | Extruded butyl rubber |
| | Surface finish: | Plastic film/aluminium |
| | Under surface finish : | Silicone film |

The manufacturer reserves the right to modify, at any time, the characteristics of this product.