

Technical Data Sheet

VAP

Air & Vapour Control Layer (AVCL)
Base & Underlayer

| | |
|---------------------------|---|
| Description | VAP is an air and vapour control layer composed of an aluminium foil bonded on to a glass-fibre backing. |
| Use | <p>An air and vapour control layer (AVCL) low permeability membrane used as part of a system to control the movement of air, water vapour and heat leakage from within the building. Can also be used as base or under layer as part of a multi layer waterproofing system.</p> <p>The choice of AVCL will depend on the degree of air and vapour pressure produced, the specified roof deck/slab and the need for a robust temporary waterproofing layer.</p> <p>VAP is suitable for use on profiled metal roof decks in mechanically fastened single ply and bitumen warm roof waterproofing systems.</p> |
| Application method | Installed loose laid with joints fully taped and sealed to form a continuous layer. |
| Storage | Rolls to be stored upright, away from heat and protected from the elements. |
| Composition | (indicative) |

| | Unit | Value |
|------------------|------------------|-------|
| Glass fibre | g/m ² | 60 |
| Aluminium 4/100° | g/m ² | 110 |
| Glue | g/m ² | <30 |
| Water absorption | | Nil |

The manufacturer reserves the right to modify, at any time, the characteristics of this product.