

Technical Data Sheet

VERNIS ANTAC GC Primer

Description	VERNIS ANTAC GC is a high performance, solvent-based, rapid drying bituminous primer specially modified with an adhesive.
Use & application method	<p>Priming of concrete, timber or metal roof deck/slab in preparation for receiving bitumen membranes.</p> <p>Average consumption: 100 - 150 g/m²</p> <p>Application by brush or roller, on dry, clean surface. Allow to dry completely before applying waterproofing membranes.</p> <p>Dust free in 15 minutes at 25°C, dry in 60 minutes at 25°C.</p> <p>Cleaning tools: petroleum solvents (e.g. white spirit).</p>
Packaging	30 L drum with a nominal weight of 30.5 kg.
Storage	<p>Store in a cool ventilated area.</p> <p>Protect from heat and keep away from any source of flame or spark.</p> <p>Maximum storage period : 2 years (in unopened original packaging)</p>
Safety information	<p>This product contains flammable products.</p> <p>Safety precautions to comply with when using this product are described in the VERNIS ANTAC GC safety data sheet. It is essential not to eat, drink or smoke while using this product. This product is harmful by inhalation, skin contact and ingestion. Do not dispose of product into drains.</p>

Characteristics	Units	Value	Tolerance
Density		0.93	± 0.05
Solid content	%	41	± 2
Viscosity at 25 °C (CF no. 4)	s	16-30	
Flash point	°C	25	± 2
Colour		Brown	
Consistency		Liquid	

The manufacturer reserves the right to modify, at any time, the characteristics of this product.