

Technical Data Sheet

WILOTEKT SURFACE CONDITIONING PRIMER

Wilotekt®-Plus Structural Waterproofing System

Introduction	Wilotekt Surface Conditioning Primer is a black, liquid, solvent-based, fast drying, bitumen primer modified with adhesive and supplied ready to use.
Usage	Bitumen-based primer used on all substrates (concrete, screeds, metal and timber) before the installation of WILOTEKT®-PLUS structural waterproofing to provide a good key for the system and to protect the substrate from moisture.
Presentation	Wilotekt Surface Conditioning Primer is packaged in 25l drums. Average consumption: 150-200 g/m ² .
Storage	Wilotekt Surface Conditioning Primer must be stored in a well ventilated area. The product must be kept away from naked flames and electrostatic charge. Shelf life (sealed in unopened, original packaging): 2 years.
Composition	Solvent phase bitumen, fast drying aromatic solvents; toluene free.
Application	By brush or roller on dry, clean surface. Allow to dry completely before applying waterproofing membrane. Drying time: 60-90 mins. Cleaning tools: petroleum solvents.

Characteristics

Density	0.94+-0.05
Solid content	54% +-2%
Viscosity at 25°C (CF no. 4)	16 - 30s
Flash point	26°C

Wilotekt®-Plus Accreditation: European Technical Assessment ETA 03/0049.

This product contains flammable products. Safety precautions to comply with when using this product are given in the Wilotekt Surface Conditioning Primer Safety Data Sheet. It is essential not to eat, drink or smoke while using this product. It is harmful by inhalation, skin contact and ingestion. Do not dispose of product into drains. For further information, contact Axter Ltd.

The manufacturer reserves the right to modify, at any time, the characteristics of its products.