

Aurora



Furlong Flooring®
First choice flooring for every room

Product Specification

PRODUCT DIMENSIONS	PLANK	HERRINGBONE	SQUARE TILE	MEDIUM TILE
Width	196mm	158mm	493mm	493mm
Length	1320mm	632mm	493mm	986mm
Number of panels per pack	14	24	14	10
m ² per pack	3.62m ²	2.4m ²	3.4m ²	4.86m ²
Weight per pack	15.09kg	9.97kg	14.16kg	20.27kg

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2.5mm	EN ISO 24346:2006-10
Wear Layer	0.55mm	EN ISO 24340:2012-02
Wear Layer Treatment	Superguard Pride®	
Thermal Resistance /Tog Rating	0.01m ² K/W / 0.1 TOG	EN 12667:2001-01
Suitability	Class 23- Heavy Domestic Class 33-Heavy Commercial	EN ISO 10874
Inflammability	Bfl-S1	EN 13501-1:2018
Scratch Resistance	MSR-A1, MSR-B1	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25mm >400mm: ≤0.35mm	EN ISO 24342:2018-11
Slip Resistance	DS/ R9 :R10	EN 13893:2002-11
Residual Indentation	Norm ≤0.1mm Average production result: 0.05 mm	EN ISO 24343-1:2012-01
Furniture Leg Resistance	No visible damage	EN ISO 16581:2019-06
Curling	Norm ≤ 2mm. Result OK	EN ISO 23999:2021-11
Dimensional stability	Norm: ≤ 0.25% Average result measured: ≤0.05 %	EN ISO 23999:2021-11
Formaldehyde Group	E1	EN 717-1:2004-10
Acoustic Insulation	3 dB	ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	ISO 4918:2016-03
Stain Resistance	OK	EN 438-2:2016+A1:2018-12
Light Fastness	Class ≥ 6	ISO 105-B02:2014-09
Underfloor Heating	Suitable, max 27°C.	EN12524
Warranty	25 Year Residential 10 Year Commercial	



Aurora




Furlong Flooring®
First choice flooring for every room


Product Specification

Aurora LVT Flooring designs are “embossed in register” for an authentic and natural feel. They offer standard plank, herringbone, and tile designs that can bring a beautifully modern feel to your home. The improved wear layer makes Aurora LVT hard-wearing, moisture-resistant, and easy to clean.


COLOURS	TILES	PLANKS	Herringbone	Slip Resistant
Thassos Stone (Square)	46506			R10
Thassos Stone (Medium Tile)	46506			R10
Tuscany Stone (Square)	46537			R10
Tuscany Stone (Medium Tile)	46537			R10
Theodore Oak		84227	84227	R9
Olive Oak		84312	84312	R9
Heathland Oak		83273	83273	R9
Laguna Oak		83853	83853	R9
Freya Oak		53256	53256	R10
Bayla Oak		53452	53452	R10
Truckee Oak		82871	82871	R10




Suitable for bathrooms




Suitable for use with underfloor heating




0.55mm wear layer



Scuff-proof coating



Residential Warranty



Slip resistant
*depending on decor please check table

Dartford: 01322 628700

Preston: 01772 316150

Stonehouse: 01452 228400

Ireland +353-1-409200

www.furlongflooring.com

enquiries@furlongflooring.com

