

Carina



Furlong Flooring®
First choice flooring for every room

Product Specification

PRODUCT DIMENSIONS	PLANK	TILES
Width	196mm	329mm
Length	1320mm	659mm
Number of panels per pack	14	16
m ² per pack	3.62m ²	3.47m ²
Weight per pack	15.19kg	14.37kg

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2.5mm	EN ISO 24346
Wear Layer	0.55mm	EN ISO 24346
Wear Layer Treatment	Superguard Pro®	
Thermal Resistance/Tog Rating	0.01m ² K/W/ 0.1 Tog	
Suitability	Class 23- Heavy Domestic Class 33-Heavy Commercial	EN ISO 10874
Inflammability	Bfl-S1	EN 13501
Scratch Resistance	≤MSR-A2, ≤ MSR-B2	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0.25mm >400mm: ≤0.35mm	EN ISO 24342b
Slip Resistance	DS/ R9 : R10	EN 13893
Residual Indentation	Norm≤0.1mm. Average result measured: 0.05mm	EN ISO 24343-1
Furniture Leg Resistance	No visible damage	EN ISO 16581
Curling	Norm:≤2mm. Result: OK	EN ISO 23999
Dimensional stability	Norm: ≤ 0.25% Average result measured: ≤0.05 %	EN ISO 23999
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	3 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	OK	EN ISO 26987
Light Fastness	Class ≥6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524
Warranty	25 Year Residential 10 Year Commercial	



Carina




Furlong Flooring®
First choice flooring for every room


Product Specification

Carina offers a stunning range of on-trend wood and natural stone designs that are suitable for all rooms in the home. With an improved wear layer of 0.55mm, Carina is moisture-resistant, hygienic, and easy to keep clean. Produced from sustainable FSC forestry and achieves Blue Angel environmental certification.


COLOURS	PLANKS	TILES	Slip Resistance
Addyston Oak	24238		R10
Jackson Oak	24126		R10
Hartville Oak	24913		R10
Dusty Oak	24321		R10
Parkerton Oak	22230		R9
Bowerston Oak	24219		R10
Yoder Oak	24867		R10
Wheatland Oak	24820		R10
Tassell Oak	24935		R10
Gettysburg Oak	22209		R9
Calendonia Oak	22851		R9
Dennison Oak	22455		R9
Grigio Stone		46906	R10
Bianco Stone		46119	R10
Dixon Stone		46905	R10
Glenrock Stone		46953	R10




Suitable for bathrooms




Suitable for use with underfloor heating




0.55mm wear layer



Scuff-proof coating



Residential Warranty



Slip resistant *depending on decor please check table

Dartford: 01322 628700

Preston: 01772 316150

Stonehouse: 01452 228400

Ireland +353-1-409200

www.furlongflooring.com

enquiries@furlongflooring.com

