



**Furlong Flooring®**  
First choice flooring for every room

## MAGNUM PRODUCT SPECIFICATION

| CONSTRUCTION      | SPECIFICATION                 | STANDARD          |
|-------------------|-------------------------------|-------------------|
| Surface Aspect    | Ribbed                        |                   |
| Yarn              | 100% PP                       |                   |
| Backing           | Rot Proof Water Resistant Gel | ISO 2424          |
| Width             | 2mtr                          |                   |
| Pile weight       | 1040 gr/m <sup>2</sup>        | ISO 8543          |
| Total Weight      | 1740 gr/m <sup>2</sup>        | ISO 8543          |
| Pile Height       | 5mm                           | ISO 1765          |
| Total Height      | 10,5mm                        | ISO 1765          |
| Roll Length       | 25m                           |                   |
| Flammability      | Efl S1                        |                   |
| Recommended Usage | Class 33 - Heavy Commercial   |                   |
| CE Compliant      |                               | EN 14041 / EN1307 |

Suitable for usage in:



Office & Corporate



Leisure & Hospitality



Housing



Hospitals & Nursing Homes



Retail



School & Further Education

Features:



BQA\_QMS019\_C\_199658



Acoustic



Anti-static



Hot Nut Tested



Underfloor Heating



Beige 1951




Anthracite 2952



Grey 2954



Red 3953



Blue 5955



Brown 7957



EN 14041  
EN 1307



**DARTFORD**  
01322 628700  
**PRESTON**  
01772 316155

**STONEHOUSE**  
01452 228480  
**DUBLIN**  
+353-1-4092000



Alternatively, visit [furlongflooring.com](http://furlongflooring.com)  
or email [enquiries@furlongflooring.com](mailto:enquiries@furlongflooring.com)

Follow us on

