



Furlong Flooring®
First choice flooring for every room

MAGNUS PRODUCT SPECIFICATION

CONSTRUCTION	SPECIFICATION	STANDARD
Surface Aspect	Chevron	
Yarn	100% PP	
Backing	Rot Proof Water Resistant Gel	ISO 2424
Width	2mtr	
Pile weight	1040 gr/m ²	ISO 8543
Total Weight	1740 gr/m ²	ISO 8543
Pile Height	5mm	ISO 1765
Total Height	7mm	ISO 1765
Roll Length	25m	
Flammability	Efl S1	
Recomended Usage	Class 33 -Heavy Commercial	
CE Compliant		EN 14041 / EN1307

Suitable for usage in:



Office & Corporate



Leisure & Hospitality



Housing



Hospitals & Nursing Homes



Retail



School & Further Education

Features:



BQA_QMS019_C_199658



Acoustic



Anti-static



Hot Nut Tested




Underfloor Heating



Beige 1951




Anthracite 2952




Grey 2954



Red 3953



Blue 5955



Brown 7957



EN 14041
EN 1307



DARTFORD
01322 628700
PRESTON
01772 316155

STONEHOUSE
01452 228480
DUBLIN
+353-1-4092000



Alternatively, visit furlongflooring.com
or email enquiries@furlongflooring.com

Follow us on

