



MANOR PRODUCT SPECIFICATION

PRODUCT INFORMATION	8MM SPECIFICATION	10MM SPECIFICATION	TEST METHOD
Collection	Manor - Herringbone	Manor - Herringbone	
Type	Laminate Classenboard HDF	Laminate Classenboard HDF	
Dimensions	643mm x 131mm x 8mm	643mm x 131mm x 10mm	
Quantity/weight per box (PU)	14 pieces=1179m ² /approx 9kg	11 Pieces =0.926m ² /approx 9kg	
Quantity/weight per pallet	96 PU=113.184m ² /approx 806kg	96 PU=88,896m ² /approx 800kg	
Geometrical characteristics	Length: ± 0.5mm Width ± 0.1mm		EN 13329
Thickness	Ø ≤ 0.5mm		EN 13329
Squareness	≤ 0.20mm		EN 13329
Straightness	≤ 0.30 mm/m		
Flatness of Elements	Width concave ≤ 0.15% convex ≤ 0.20% Length: concave ≤ 0.50% convex ≤ 1.00%		EN 13329
Openings	Ø ≤ 0.15mm -Max. ≤ 0.20mm		EN 13329
Height Difference	Ø ≤ 0.10mm -Max. ≤ 0.15mm		EN 13329
Residual Indentation	≤ 0.05mm		EN ISO 24343-1
Light Fastness	grey scale level ≥ 4		EN ISO 4892-2
Wear Resistance	≥ 6000 cycles (AC 5)		EN 13329
Impact Resistance	small - diameter ball ≥ 35mm large - diameter ball ≥ 750mm		EN 17268 EN 13329
Castor chair resistance	no damage with type W after 25 000 cycles		EN 425
Thickness Swelling	≤ 18%		ISO 24336
Locking Strength	F _{10.2} ≥ 1.0 kN/m F _{s0.2} ≥ 2.0 kN/m		ISO 24334
Movement of Furniture Leg	no damage with type 0		ISO 24334
Resistance to Staining	5 (group 1 & 2), 4 (group 3)		EN 438-2
Surface Soundness	≥ 1.25 N/mm ²		EN 13329
Reaction of fire*	C _{fl-s} 1		EN 923-1
Slip Resistance*	DS		EN 13893
Electrostatic Behaviour*	≤ 2 kV		EN 1815
Formaldehyde*	E1		EN 16516
Formaldehyde - Emissions	US EPA TSCA Title VI / CARB P 2		ASTM D6007
VOC Emissions	A+		Décret no 2011-321
Thermal Conductivity*	≥ 0.075 W/mK		EN 12667
Thermal Resistance*	R ≤ 0.06 (m ² K)/W		





Furlong Flooring®
First choice flooring for every room

MANOR PRODUCT SPECIFICATION

COLOURS	ITEM
Oak Greige	62663
Oak Beige	62704
Oak Natural Beige	62705
Oak Light Brown	62706
Oak Light Natural	62707
Oak Dark Natural	62708
Oak Chocolate Brown	62709
Oak Black	62710
Mettray -8mm only	63061



Free 20 year wear and stain warranty for complete peace of mind. (Domestic)




Suitable for use with underfloor heating



Eco friendly flooring



AC5 -Highest Durability rating



Megaloc Twin



DARTFORD
01322 628700
PRESTON
01772 316155

STONEHOUSE
01452 228480
DUBLIN
+353-1-4092000



Alternatively, visit furlongflooring.com or email enquiries@furlongflooring.com

Follow us on

