



**Furlong Flooring®**  
First choice flooring for every room

## PICTORA III PRODUCT SPECIFICATION

PRODUCT INFORMATION	PRODUCT SPECIFICATION
Type	Vinyl
Backing	Foam
Widths	2m/3m/4m
No. of Patterns	13
Thickness	2.80
Wear Layer	0.20mm
Wear Layer Treatment	Natural Feel
Total Weight	1600g/m <sup>2</sup>
Guarantee	5 Years
Slip Resistant	R10
European Class EN ISO 10874	22
Standard Roll length	30m
Standard Roll Weight	100kg (2m), 150kg (3m), 200kg (4m)
Acoustic Insulation	18dB
Suitable for underfloor heating EN 12524	Yes
Inflammability	cf1-S1
Thermal Resistance	0,0112 m <sup>2</sup> K/W / 0.11 TOG
Thermal Conductivity	0,25 W / mK
Resistance to household chemicals	Very good





# Furlong Flooring®

First choice flooring for every room

## PICTORA III PRODUCT SPECIFICATION

COLOURS	FORMAT	COLOUR ID	Pattern repeat	Plank/Tile size
BLUE FLORA	TILE	GP401	99.5 x100	20 x 20
GREY FLORA	TILE	GP402	99.5 x100	20 x 20
OCTAGRAM	TILE	GP403	99.5 x100	16.7 x 16.7
ECCENTRIC	TILE	GP404	99.5 x100	16.6 x 16.6
DIAMETRIC	TILE	GP405	99.5 x100	N/A
BLACK QUARTZ	TILE	GP406	99.5 x100	33.3 x 20
LIGHT ECHO	TILE	GP407	99.5 x100	20 x 33.33
STONE REPRISE	TILE	GP408	99.5 x100	25 x 40
GREY TILT	TILE	GP409	99.5 x100	17.7 x 35.3
STEEL PANE	TILE	GP410	100 x 100	N/A
DIVIDE	TILE	GP411	100 x 100	33.3 x 33.3
ENHANCE TILE	TILE	GP412	100 x 100	33.3 x 33.3
VILLA GREY	TILE	GP413	100 x 100	16.6 x 16.6
AUTHENTIC STONE	TILE	GP414	99.5 x 120	25 x 40
TABULAR LIGHT	TILE	GP415	99.5 x 100	N/A



Easy to Care



Suitable for bathrooms



Slip Resistant



Sound Absorbing



**DARTFORD**  
01322 628700  
**PRESTON**  
01772 316155

**STONEHOUSE**  
01452 228480  
**DUBLIN**  
+353-1-4092000



Alternatively, visit [furlongflooring.com](http://furlongflooring.com) or email [enquiries@furlongflooring.com](mailto:enquiries@furlongflooring.com)

Follow us on

