



SIRONA PRODUCT SPECIFICATION

PRODUCT INFORMATION	PRODUCT SPECIFICATION	
Construction	PVC	
Thickness	2 mm	EN ISO 24346
Wear Layer	0,3mm	EN ISO 24340
Wear Layer Treatment	Superguard®	
Total Weight	3328 g/m ²	EN ISO 23997
Plank Size	16,3 x 98,8cm	EN ISO 24342
Planks per box	24pcs/box	3,87m ² /box
Tile size	32,9 x 65,9cm	EN ISO 24342
Box Tiles	18pcs/box	3,9m ² /box
Tog Rating	0.1	
Suitability	Class 23- Heavy Domestic Class 31-Light Commercial	EN ISO 10874
Imflammability	Bfl-S1	EN 13501
Abrasion Group	Class T	EN ISO 660-2
Scratch Resistance	≤MSR-A2, ≤MSR-B2	EN ISO 16094
Squareness & Straightness	≤400mm: ≤0,25mm >400mm: ≤0,35mm	EN ISO 24342b
Slip Resistance	DS	EN 13893
Slip Restraint	R10	DIN 51130
Residual Indentation	Norm ≤0,10mm Average result measured: 0,03mm	EN ISO 24343-1
Furniture Leg Resistance	No Cracks, No Damage	EN ISO 16581
Curling	Norm: ≤1 2 l mm. Result: ≤2mm	EN ISO 23999
Electrial Resistance	≤10° Ohm	EN 1081
Dimensional stability	Norm: ≤ 0,25 % Average result measured: ≤0,05%	EN ISO 23999
Heat Insulation	0,25 w/(m.K)	EN ISO 10456
Thermal Resistance	0,01 m ² . K/W	EN 12667
Electrostatic Performance	< 2 kV	EN 1815
Formaldehyde Group	E1	EN 717-1
Acoustic Insulation	4 dB	EN ISO 717-2
Castor Chair Resistance	No damage to wear layer, no delamination	EN ISO 4918
Stain Resistance	Very Good	EN ISO 26987
Light Fastness	≥6	EN ISO 105-B02
Underfloor Heating	Suitable, max 27°C	EN 12524





Furlong Flooring®

First choice flooring for every room

SIRONA PRODUCT SPECIFICATION

COLOURS

Little Rock Pine 24115
Jonesboro Pine 24242
Springdale Pine 24966
Danville Oak 24279
Emerson Oak 22931
Oakland Oak 24243
Mayflower Oak 24929
Waldron Stone 46913
Viola stone 46931
Berryville Oak 24241
Caraway Oak 24856
Glenwood Oak 22912
Kensett Oak 24235
Hoxie Oak 24935
Ravenden Stone 46945
Tillar Stone 46960



Suitable for bathrooms



Free 20 year residential warranty



0.3mm wear layer.



Better sound insulation



Slip Resistant



DARTFORD
01322 628700
PRESTON
01772 316155

STONEHOUSE
01452 228480
DUBLIN
+353-1-4092000



Alternatively, visit furlongflooring.com or email enquiries@furlongflooring.com

Follow us on

