



Furlong Flooring®
First choice flooring for every room

TUNGSTEN VELOUR PRODUCT SPECIFICATION

CONSTRUCTION	SPECIFICATION	STANDARD
Surface Aspect	Velour	
Yarn	100% PP	
Backing	Rot Proof Water Resistant Gel	ISO 2424
Width	4mtr	
Pile weight	650 gr/m ²	ISO 8543
Total Weight	1195gr/m ²	ISO 8543
Pile Height	3mm	ISO 1765
Total Height	7,5mm	ISO 1765
Roll Length	30m	
Flammability	Efl S1	
Recommended Usage	Class 33 - Heavy Commercial	
CE Compliant		EN 14041 / EN1307

Suitable for usage in:



Office & Corporate



Leisure & Hospitality



Housing



Hospitals & Nursing Homes



Retail



School & Further Education

Features:



BQA_QMS019_C_199658



Acoustic



Anti-static



Hot Nut Tested



Underfloor Heating



Beige 1153




Red 3353



Midnight 5507



Ensign Blue 5524




Anthracite 2236



Willow 6627



Steel 2531



Autumn Glow 7745



Frost Grey 2067



EN 14041
EN 1307



DARTFORD
01322 628700
PRESTON
01772 316155

STONEHOUSE
01452 228480
DUBLIN
+353-1-4092000



Alternatively, visit furlongflooring.com
or email enquiries@furlongflooring.com

Follow us on

