



**Furlong Flooring®**

First choice flooring for every room

# Timeless Classic

## PRODUCT SPECIFICATION



Add the natural touch of wool to your home

CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted, cut pile	
Yarn	80% Wool, 10% Polyester, 10% Meltbond	BS ISO 1833
Machine Gauge	1/8 Gauge	
Width	4 & 5 Mtrs	
Tuft Density	129,400 tufts/ m <sup>2</sup>	BS ISO 1763:2020
Total Weight	2400grms	BS ISO 8543:2020
Inserted Weight	1356grms	BS ISO 8543:2020
Pile Height	8mm (±10%)	BS ISO 1766:1999
Total Thickness	11mm (±10%)	BS ISO 1765:1986
Standard Roll Length	30 linear meters	
Type of Backing	Combi Bac®	
Classification	Class 22-General Domestic	BS EN 1307:2014
	Luxury Class 4	BS EN 1307:2014
Thermal Resistance	1.5 TOG / 0.150m <sup>2</sup> K/W	BS 4745:2005 (ISO 5085-1:1989)
Hot Metal Nut Test	Low Radius of Char	BS 4790:1987 (2014)
Flammability	Cfl S1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12

### WARRANTY

Wear 10 years

Biological Moth Resistant



Tranquil Truffle  
4101



Light Lace  
4102



Pure Pebble  
4107



Sand Salt  
4103



Classic Clay  
4104



Mild Malt  
4105



Fleeting Fawn  
4108



Cotton Cloud  
4112




Cool Chrome  
4113



Hessian Hue  
4106



Dawlish Driftwood  
4109



Rocky Ridge  
4114




Wilting Willow  
4110



Shimmering Sea  
4111



Soft Seaweed  
4115



Stormy Sky  
4116



inspired  
by nature



[www.furlongflooring.com](http://www.furlongflooring.com)

