



Furlong Flooring®
First choice flooring for every room

Timeless Deluxe

PRODUCT SPECIFICATION



Add the natural touch of wool to your home


CONSTRUCTION	SPECIFICATION	STANDARD
Pile	Tufted, cut pile	
Yarn	80% Wool, 10% Polyester, 10% Meltbond	BS ISO 1833
Machine Gauge	1/8 Gauge	
Width	4 & 5 Mtrs	
Tuft Density	150,800 tufts/ m ²	BS ISO 1763:2020
Total Weight	2600grms	BS ISO 8543:2020
Inserted Weight	1695grms	BS ISO 8543:2020
Pile Height	9mm (±10%)	BS ISO 1766:1999
Total Thickness	12mm (±10%)	BS ISO 1765:1986
Standard Roll Length	30 linear meters	
Type of Backing	Combi Bac®	
Classification	Class 23-Heavy Domestic Class 32 - General Commercial	BS EN 1307:2014
	Luxury Class 5	BS EN 1307:2014
Thermal Resistance	1.6 TOG / 0.160m ² K/W	BS 4745:2005 (ISO 5085-1:1989)
Hot Metal Nut Test	Low Radius of Char	BS 4790:1987 (2014)
Flammability	Cfl S1	BS 13501-1:2007
Colour Fastness to Light	4/5	BS ISO 105-X12

WARRANTY

Wear	10 years
Biological	Moth Resistant



Tranquil Truffle
5101



Light Lace
5102



Pure Pebble
5107



Sand Salt
5103



Classic Clay
5104



Mild Malt
5105



Fleeting Fawn
5108



Cotton Cloud
5112



Cool Chrome
5113




Hessian Hue
5106



Dawlish Driftwood
5109



Rocky Ridge
5114




Wilted Willow
5110



Shimmering Sea
5111



Soft Seaweed
5115



Stormy Sky
5116



inspired
by nature

