
				CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland				Name and address of manufacturer
DOP01REV3 MEDITE PREMIER L-MDF				DoP reference.
EN 13986:2004 +A1:2015				Reference to harmonised standard
Not Applicable				Notified body number
04				Year in which the CE mark was first affixed
E1				Formaldehyde classification
L-MDF				Product technical class
Internal use as non-structural components in dry conditions				Intended use
Thickness Range mm	9 to 12	>12 to 19	>19 to 25	Thickness range
Internal bond (N/mm²)	0.45	0.45	0.45	Declared performance
Swelling in thickness %	16	14	12	
Reaction to fire	D-s2,d0	D-s2,d0	D-s2,d0	
Release of formaldehyde	E1	E1	E1	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	
Biological	Use Class 1			

						CE symbol
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland						Name and address of manufacturer
DOP02REV3 MEDITE PREMIER MDF						DoP reference.
EN 13986:2004+A1:2015						Reference to harmonised standard
Not Applicable						Notified body number
04						Year in which the CE mark was first affixed
E1						Formaldehyde classification
MDF						Product technical class
Internal use as non-structural components in dry conditions						Intended use
Thickness Range mm	3 to 4	>4 to 6	>6 to <9	>25 to 30	>30 to 45	Thickness range
Internal bond (N/mm²)	0.65	0.65	0.65	0.55	0.50	Declared performance
Swelling in thickness %	35	30	17	10	8	
Reaction to fire	NPD	NPD	NPD	D-s2,d0	D-s2,d0	
Release of formaldehyde	E1	E1	E1	E1	E1	
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	
Biological	Use Class 1					