

**DECLARATION OF PERFORMANCE  
MEDITE EXTERIOR**Reference Number: **CADOP07****MEDITE EUROPE DAC****Redmondstown****Clonmel****County Tipperary****Ireland**


Product Type	Intended Use	AVCP*	Approved Body Reference
MDF.H-2	External use as non-structural components	4	Not Applicable
*Assessment and verification of constancy of performance system according to Annex V of regulation (EU) No 305/2011			

**Declared Performance**

Essential characteristics	Performance						Designated Standard
	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	
Thickness Range							EN 13986:2004+A1:2015
Internal bond (N/mm <sup>2</sup> )	0.70	0.70	0.80	0.80	0.75	0.75	
Moisture Resistance Internal bond after boil test (N/mm <sup>2</sup> )	0.20	0.20	0.15	0.15	0.12	0.12	
Thickness Swelling (24hrs) %	30	18	12	10	8	7	
Release of formaldehyde	E1	E1	E1	E1	E1	E1	
Reaction to fire	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	
Water vapour permeability $\mu$	NPD	NPD	NPD	NPD	NPD	NPD	
Airborne sound insulation (surface mass) (R)	NPD	NPD	NPD	NPD	NPD	NPD	
Thermal conductivity	NPD	NPD	NPD	NPD	NPD	NPD	
Biological durability	Use Classes 1,2 & 3						
Release (content) of pentachlorophenol (PCP)	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	

This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011 as it has effect in the United Kingdom in respect of Great Britain, under the sole responsibility of the manufacturer identified above

Signed for and on behalf of the manufacturer by:



Tom Prendergast, Technical Manager.

Clonmel, Ireland. 12/07/2021