

							
MEDITE, Redmondstown, Clonmel, Co. Tipperary, Ireland							
CEDOP03 MEDITE MR MDF.H-1							
EN 13986:2004+A1:2015							
Not Applicable							
04							
E1							
MDF.H-1							
Internal use as non-structural components in humid conditions							
<b>Thickness Range mm</b>	3 to 4	>4 to 6	>6 to 9	>9 to 12	>12 to 19	>19 to 30	>30 to 45
<b>Internal bond (N/mm<sup>2</sup>)</b>	0.70	0.70	0.80	0.80	0.75	0.75	0.70
<b>Swelling in thickness %</b>	30	18	12	10	8	7	7
<b>Internal bond after cyclic test (N/mm<sup>2</sup>)</b>	0.35	0.35	0.30	0.25	0.20	0.15	0.10
<b>Swelling in thickness after cyclic test %</b>	40	25	19	16	15	15	15
<b>Reaction to fire</b>	NPD	NPD	NPD	D-s2,d0	D-s2,d0	D-s2,d0	D-s2,d0
<b>Release of formaldehyde</b>	E1	E1	E1	E1	E1	E1	E1
<b>Release (content) of pentachlorophenol (PCP)</b>	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm	≤5ppm
<b>Biological</b>	Use Class 1 & 2						

CE symbol

Name and address of manufacturer

DOP reference

Reference to harmonised standard  
Notified body number

Year in which the CE mark was first affixed

Formaldehyde classification

Product technical class

Intended use

Thickness range

Declared performance